



SCALE STEEL PLATFORM

TS3 Simplon pit type Truck Scale is with full steel platform, it is a scale model that can increase the maneuverability of the vehicles, which does not take up space on the ground, in the narrow spaces mounted under the ground, especially in factory entrances, and that can operate without problems for many years.

IPE type steel is used on the platform, the top covering sheet is at least 10 mm thick.

TS3 Pit Truck Scale is suitable for heavy duty conditions such as mining, agriculture, livestock, construction and steel industry.

SCALE TERMINAL

The i5 weighing indicator that we use in Ts3 Simplon dimple type truck scale is a robust and reliable weighing indicator with high precision 24 bit sigma delta ADC, with antivibration filtering software and stable weighing features.

Legally more accurate weighing with two-stage weighing feature.

1/30000 ADC cycle sensitivity, 26 mm high backlit LCD display.

SCALE PROGRAM

Using Kobastar Windows based scale program is very simple and easy.

It is simple to use for anyone who knows how to use a computer, but with its powerful database, it has data sending and reporting functions in xml, excel, pdf, html, txt formats.

It provides remote traceability with the optional web-based database.

Light management and license plate reading systems can be easily integrated.

LOAD CELLS

Print type 30 ton capacity OIML R60 C4 certified.

With its stainless steel body and IP68 protection, it is extremely resistant to adverse environmental conditions and corrosion.

It provides protection from lateral loads with standard mounting kits and prevents false weighing.

Optionally, KOBASTAR TSD model digital load cells are also used.

MODEL	SIZES (m.)	LOAD CELL COUNT	CAPACITY TON	DIVISION (Kg.)
TS-3-364	3X6	4	40	10/20kg.
TS-3-384	3X8	4	40-50-60 t	10/20kg
TS-3 -3106	3X10	6	40-50-60 t	10/20kg
TS-3 -3126	3X12	6	40-50-60 t	10/20kg
TS-3 -3146	3X14	6	60-80 t	20kg-50kg.
TS-3 -3168	3X16	8	60-80-100 t	20kg-50kg.
TS-3 -3188	3X18	8	60-80-100 t	20kg-50kg.
TS-3 -3208	3X20	10	60-80-100 t	20kg-50kg.
TS-3 -3228	3X22	10	60-80-100 t	20kg-50kg.